

Complete Units

Model 7053 F90

Order no 403062



Use

Model 7053 F90 is a complete window counter and transfer unit, with a Model 53 F90 pass-through for use in indoor and outdoor areas that comes ready for installation. It is ideal for indoor use as a sales or reception counter for places such as front-desk receptions, gatehouses or for handing over passes, receipts, firearms and similar items in areas requiring a high level of firearms protection.



Safety and features

- Window unit with sliding Model 53 F90 pass-through for pedestrians, fits flush with outside façade. Front panel for handing over flat items such as passes, receipts, passports and other items up to 32 mm high, and an integrated intercom for automatic two-way conversation.
- Drawer locks automatically when closed.
- Materials offer fire protection adhering to F90** and FB4* firearms protection capable of withstanding heavy handgun fire and more than 90 minutes of exposure to smoke and fire at up to 1000°C.
- Model 7053 F90 fulfils German UVV regulations.

Materials and use

- Safety glass adhering to BR4 NS and Promaglas 90/37 Type 1.
- Frame made of 2 mm brushed stainless steel.
- Cover panel made of 1 mm brushed stainless steel, cover made of 2 mm brushed stainless steel.
- All metal parts have been produced using state-of-the-art precision laser cutting technology for ultimate quality.
- Model 7053 F90 is suitable for use in outdoor areas.
- The unit requires no maintenance. No need for cleaning or lubrication.

** The Model is part of the tested model 7553 F90

* Series comes with certificate

Complete Units

Outer dimensions (all measurements in mm)

Width	1040
Height	1270
Depth	552

Drawer clearance

Width	320
Depth	265
Height	32

Mounting, wall recess

990 x 1200 (W x H)

Weight

280 kg

Miscellaneous

- Available in higher firearms-protection classes, eg: FB6
- Available as Model 7053H F90 with higher drawer clearance of 120 mm.
- Also available with window shutters and illumination
- Special sizes available on request
- Frame coatings available in alternative RAL colours on request

Walter Wurster GmbH

Heckenrosenstraße 38
 D-70771 Leinfelden-Echterdingen
 Telefon: +49 (0) 711 / 9 49 62-0
 Telefax: +49 (0) 711 / 7 97 72 90
 e-mail: info@wurster.com
 internet: www.wurster.com

Modell 7053 F90

Installation and dimensions

The window unit comes complete with power cables and is ready for exact mounting in prepared wall sections. It is inserted into the recess from the outside to fit flush with the wall. This is done by removing the inner frame before screwing the unit into place from the inside to prevent tampering. Consideration must be given to access requirements and the possible need to remove the unit later in the unlikely event of repairs. There should be a 230 V socket near the counter on the inner side.

